






























(October, 2022)

ITEM	Picture	Description	Standard	Countries that imported this product
Patient ventilator, intensive care, for adult and pediatric		Boaray 5000D; 20-2000ml (VCV); Applicable to adult, pediatric and infant, Various ventilation modes for different needs of all patients low noise. World leading brands of key components of ventilator ensure high accuracy and stable performance. Ventilation frequency: 1-100 bpm; Pressure support:0-70 cm H2O; Nebulizer: 30 minutes; Alarm:Audio and visual alarms with three levels ; Competitive price and quick delivery.	93/42/EEC ISO13485	Nigeria, Russia, Germany, ect.
Bi pap Device Note: Bi pap device+oxygen concentrator=non-invasive ventilator ; These 2 items can be supplied separately or together.		Target Tidal volume: 100-2000ml Pressure increment: 0.2cmH2O Altitude compensation: Automatic Sound Levels: <28dB(A) Languages: Multi-languages Ramp time :0~60min Data storage :4GB (store data of 4 years long) Warranty: 2 years for host Display 5"LCD with touchable screen Power supply input: 100-240VAC, 50/60Hz, 1.5A Output: 24VDC, Dimensions(LxWxH) 271.5*143*139.5mm Competitive price and quick delivery. On China Customs white list	EUA, MDD93/42/EEC IEC60601-1 ISO8185:2007 ISO80601-2-70	Brazil, Spain,France,South Africa,Poland etc.
Oxygen Concentrator Note: Bi pap device+oxygen concentrator=non-invasive ventilator ; These 2 items can be supplied separately or together.		Flow : 1L-5LPM Voltage/Frequency : 220V/50Hz±1Hz or 115V/60Hz Pressure : (40-60) kPa Oxygen purity : 93%±3% Power Consumption: 300VA Noise: <45dB(A) Size:470*370*590mm Competitive price and quick delivery. On China Customs white list	EUA, MDD93/42/EEC IEC6 0601-1 ISO8185:2007 ISO80601-2-70	
Alcohol-based hand sanitizer		100ml GeL, 75% alcohol	SDS Report ISO22716	USA,, France, Portugal,etc.
		500ml GeL, 75% alcohol	US FDA CFSAN Cert	
Alcohol-based hand sanitizer		100ml GeL, ethyl alcohol 75%	SDS report by TUV; Certificate for safe transport of goods;	Britain, US A,, Australia, ect.
		500ml GeL,ethyl alcohol 75%	certificate of hazard classification and identification for chemicals.	
RESPIRATOR, mask, FFP2/N95		Medical rated, Individual package , On China Customs white list	FDA Class II EN149 GB2626-2006 CE Module B CE Module C2	Argentina, USA, Italy, Spain, ect
RESPIRATOR, mask, FFP2/N95		Medical rated, competitive price	FDA Class II EN149 GB2626-2006	France, Canada, Portugal, etc.
MASK, MEDICAL / SURGICAL, Type II or higher		Type I Type II Type IIR	FDA class II EN14683 Canada MDEL	France, Canada, Portugal, etc.
MASK, MEDICAL / SURGICAL, Type II or higher		Type I, Non-woven20g+Meltblown20g+Non-woven20g size:175*95mm; Type II, Non-woven20g+Meltblown20g+Non-woven20g size:175*95mm; TYPE IIR, Non-woven20g+Meltblown20g+Non-woven20g size:175*95mm;	FDA class II; ISO13485; EN14683	Australia, USA, Japan,ect.




(October, 2022)

ITEM	Picture	Description	Standard	Countries that imported this product
Goggles, Protective		Lens thickness 1.5mm, injection molding PC material, can pass the international UV400 test. The frame is made of medical equipment grade pure PVC, with moderate hardness of 70 degrees, no odor, no fog Frame: PVC, lens: anti-fog PC	ANSI/ISEA Pass Z87.1-2015 Test	Spain,ect.
Goggles, Protective		Frame: PVC, lens: anti-fog PC Feature:disposable Size:155×60mm Packing standard:1piece/bag , 200pieces/carton	ANSI/ISEA Pass Z87.1-2015 Test MDD 93/42/EEC ISO13485	Sweden,USA,ect.
Face Shield		Material:Polymer material,anti fog Feature:disposable Size:22×33cm Packing standard: 1piece/bag, 250pieces/carton	EN166 ANSI/ISEAZ87.1 GB14866-2006 ISO13485 MDD 93/42/EEC	Sweden,USA,ect.
Face Shield		Material:100% PET double side anti-fog, heat- resistant,ani-deformation; size:250*320*220mm	Module B EN166 ANSI/ISEA Z87.1 ISO9001; ISO14001	Italy ,ect.
Protective Gown, size: S,M,L,XXL;		surgical rated; Material: 45g; SMS waterproof; Flame retardant; Impermeable , On China customs white list	FDA CLASS I AAMI PB70 ISO14001 ISO9001	Russia,Canada,USA,Japan,ect
		surgical rated; PP+PE, 45g; waterproof; Flame retardant; On China customs white list	FDA CLASS I AAMI PB70 ISO14001 ISO9001	Russia,Canada,USA,Japan,ect
		surgical rated; SMS 35g; waterproof; Flame retardant; On China customs white list	FDA CLASS I AAMI PB70 ISO14001 ISO9001	Russia,Canada,USA,Japan,ect
Protective Gown, size: S,M,L,XXL;		surgical rated, PP+PE 30g; On China customs white list	EN13795-1:2019; AAMI PB70:2012 level 2-3	USA, Japan,Germany,ect
		surgical rated ; SMS 35g; On China customs white list	EN13795-1:2019; AAMI PB70:2012 level 2-3	USA, Japan,Germany,ect
Gown, Surgical/Isolation size: S,M,L,XXL		SMS(Spunbond + Meltblown + Spunbond Nonwovens),45g, On China customs white list	FDA Class II	USA,ect
		PP(Polypropylene)+PE(Polyethylene),40g, On China customs white list	FDA CLASS I ISO13485	USA,ect
		SMS(Spunbond + Meltblown + Spunbond Nonwovens),35g, On China customs white list	FDA CLASS I ISO13485	USA,ect




(October, 2022)

ITEM	Picture	Description	Standard	Countries that imported this product
Infrared thermometer		Measuring range: Human body: (32.0~43°C)/(89.6~109.4)°F Object: (5~95)°C/(41~203)°F Accuracy: Human body:(35~42)°C Outside ±0.3°C/±0.6°F Within±0.2°C/±0.4°F ; Object: ±1.0°C/±0.1°F, On China customs white list	93/42/EEC ISO13485	Italy ,ect.
Infrared thermometer		R5, size:150mm*42mm*41mm; N.W.: 95g temperature scale and tolerance: 32C~34.9C: +/- 0.3°C; 35C~42C : +/- 0.2°C; 42.1C~42.9C : +/- 0.3°C ; On China customs white list	FDA CLASS 1; IEC60601-1; ISO80601-2; ISO13485	USA,ect.
		R6,size:160mm*100mm*40mm; N.W.: 140g temperature scale and tolerance: 32C~34.9C: +/- 0.3°C; 35C~42C : +/- 0.2°C; 42.1C~42.9C : +/- 0.3°C; On China customs white list	FDA CLASS 1; IEC60601-1; ISO80601-2; ISO13485	USA,ect.
		R9,size:140mm*38mm*38mm; N.W.: 67.5g temperature scale and tolerance: 32C~34.9C: +/- 0.3°C; 35C~42C : +/- 0.2°C; 42.1C~42.9C : +/- 0.3°C; On China customs white list	FDA CLASS 1; IEC60601-1; ISO80601-2; ISO13485	USA,ect.
COVID-19 Antigen Rapid Test, Pack Size: Single		<ul style="list-style-type: none"> • Time for Results - 15 min • Relative Sensitivity - 97.14% • Relative Specificity - 99.3% • Value Accuracy - 99.06% • Disposable - Yes, single use 	CE Marked ISO13485	Thailand,Russia,Czech,ect
COVID-19 Antigen Rapid Test, Pack Size: pack of 20		<ul style="list-style-type: none"> • Time for Results - 15 min • Relative Sensitivity - 97.14% • Relative Specificity - 99.3% • Value Accuracy - 99.06% • Disposable - Yes, single use 	CE Marked ISO13485	Thailand,Russia,Czech,ect
ICU Bed		Max weight capacity (kg and lbs.) - 250 kg (552 lbs.); Siderails - split, collapsible; Adjustable height (min and max cm) - 45 to 79.; Removable Mattress - 193 cm x 90 cm x 10 cm, PVC waterproof; Powered patient positions - Trend, Reverse Trend, Fowler, semi-Fowler; Nurse controls - Footboard embedded lockout.	CE Marked ISO13485	Spain,Thailand,ect.
Medical/Surgical Bed		Max weight capacity (kg and lbs.) - 250 kg (552 lbs.); Adjustable height (min and max cm) - 45 to 79.; Removable Mattress - 192 cm x 90 cm x 10 cm, PVC waterproof; Powered patient positions - Trend, Reverse Trend, Fowler, semi-Fowler; Nurse controls - Footboard embedded lockout	CE Marked ISO13485	Spain,Thailand,ect.

(October, 2022)

ITEM	Picture	Description	Standard	Countries that imported this product
<p>Diagnostic Set Pack 1 For Woman and Child</p>		<p>Solution: screening for anemia and bone metabolism in women and children to monitor immunity. Inclusion: ①.1 Tele Medical Monitor -10.1 inch touch screen; -New design and stable for placing; -New software and more functions; -Fast Test and Easy to Use; -Realtime data exchange; -Superior accurate test result -Rechargeable lithium battery backup for 5 hours. ①.2 Accessories: 1. 12 lead ECG; 2. NIBP; 3. Infrared forehead TEMP; 4. SPO2; 5. HR/PR; 6. Backpack ② In vitro diagnostic devices to use with: 1)Hemoglobin Analyzer+HB strip (One bottle free along with device) 2)Immunofluorescence Analyzer+Strips(10pcs each free along with device) 3)Fetal Doppler, for monitoring fetal heart rate 4)Stethoscope, for checking heart and lung sound 5)weight scale, for Body mass index</p>	<p>ISO13485, CE, FDA</p>	<p>Italy ,Switzerland, etc.</p>
<p>Diagnostic Set Pack 2 For people with chronic diseases (middle-aged and elderly)</p>		<p>Solution: For long-term monitoring of chronic diseases in the middle-aged and elderly, including hypertension, hyperlipidemia, hyperuricemia, diabetes and liver and kidney diseases, as well as monitoring of anemia and bone metabolism in the middle- aged and elderly Inclusion: ①.1 Tele Medical Monitor -10.1 inch touch screen; -New design and stable for placing; -New software and more functions; -Fast Test and Easy to Use; -Realtime data exchange; -Superior accurate test result -Rechargeable lithium battery backup for 5 hours. ①.2 Accessories: 1)12 lead ECG; 2)NIBP; 3)Infrared forehead TEMP; 4) SPO2; 5) HR/PR 6) Backpack ② In vitro diagnostic devices to use with: 1)Immunofluorescence Analyzer+Strips(10pcs each free along with device) 2)Dry Biomedical Analyzer+strips (10pcs each free along with device) 3)Spiro-meter, for chronic respiratory diseases,chronic obstructive pulmonary disease,etc. 4)Stethoscope, for checking heart and lung sound 5)weight scale, for Body mass index</p>	<p>ISO13485, CE, FDA</p>	<p>Italy ,Switzerland, etc.</p>
<p>Diagnostic Set Pack 3 For Common Diseases (Full set)</p>		<p>Solution: For diagnosis of common diseases, upper respiratory tract, chronic diseases, anemia, bone metabolism, liver and kidney functions, etc Inclusion: ①.1 Tele Medical Monitor -10.1 inch touch screen; -New design and stable for placing; -New software and more functions; -Fast Test and Easy to Use; -Realtime data exchange; -Superior accurate test result -Rechargeable lithium battery backup for 5 hours. ①.2 Accessories: 1)12 lead ECG; 2)NIBP; 3)Infrared forehead TEMP; 4) SPO2; 5) HR/PR; 6) Backpack. ② In vitro diagnostic devices to use with: 1)Hemoglobin Analyzer+HB strip (One bottle free along with device) 2)WBC Analyzer +HB strips(One bottle free along with device) 3)Immunofluorescence Analyzer+Strips(10pcs each free along with device) 4)Dry Biomedical Analyzer+strips (10pcs each free along with device) 5)Urine Analyzer+strips(One bottle free along with device) 6)Spiro-meter, for chronic respiratory diseases,chronic obstructive pulmonary disease,etc. 7)Stethoscope, for checking heart and lung sound 8)Portable Ultrasound 9)weight scale, for Body mass index</p>	<p>ISO13485, CE, FDA</p>	<p>Italy ,Switzerland, etc.</p>

(October, 2022)

ITEM	Picture	Description	Standard	Countries that imported this product
Portable Words Room		Fold: 830*850*1270mm Unfold:2500*2500*2170mm Temperature:20-27℃ Fresh air Volume>=150m³/h Ventilation Frequency>=12 times/h Filtration rate>=99.99% Power Supply:AC220V/50Hz Power: Air Pressure system<=200W Air Pressure system+cooling mode<=1300W Air Pressure system+heating mode<=1300W	ISO13485, CE, FDA	USA ,Germany, etc.
Air Stabilizer		920*690*1525mm Power:500W Clear Air Volume(m³/h): 900-1800(ST18),900-2500(ST25) Noise(dB): 34-50(ST18),34-56(ST25) Air Purifying Rate>99.99%(Particulate matter>0.3) Sterilization rate: 100% for Staphylococcus Albus /klebsiella Pneumoniae 99.99% for Influenza A virus subtype H1N1/HCoV-229E	ISO13485, CE, FDA	USA and Germany, etc.
Laminar Flow Clean Room		Inner dimension of the unfolded cover :L:2466*W:(1400~2400)*H:(1750~2190)(the width is adjustable and height can be customized) Overall dimension: L:2480*W:(1450~2450)*H:(2000~2400)(the size mentioned above does not include smart plasma sterilization station. The width is adjustable and height can be customized) Achieve and maintain Class 100 Laminar: 2-3 minutes Clear Air Volume(m³/h): 900-1800(ST18),900-2500(ST25) Total number of Colony Count <5 CFU/m³ Fungal Colony Count<1CFU/m³ Sterilization rate of PM0.3>99.99% Air Changes Amount(times/h): ≧ 135(ST18), ≧ 190(ST25)	ISO13485, CE	USA and Germany, etc.

For Inquiry: info@sinoventure.net